

## Specification



### **Acrylitex Field Marking Paint**

**Manufacturer:** Acrylic Technologies, Inc.  
8914 NE Alderwood Road  
Portland, Oregon 97220  
Phone: 503.282.2591 / Fax: 503.552.1441  
[www.acrylitex.com](http://www.acrylitex.com)

**Product Description:** Acrylitex Field Marking Paint is a vinyl acrylic latex product used for line striping on natural grass and synthetic playing fields. May also be used on gravel, cinder and dirt. Easy to apply, fast drying and environmentally friendly for line marking. This product has high coverage and opacity properties to provide solid line striping. This material is non-toxic and low VOC.

**Coverage:** Approximately 300 square feet per gallon / 650-800 linear feet per 3 inch line. Coverage rates will vary with mil thickness, applicator technique and type of spray tip (amount of fallout).

**Recommended Mil Rate:** Apply 8-10 wet mils. Average dry time is 15-30 minutes dependent on air temperature and relative humidity. Recoat 2 hours.

**Packaging:** Available in 5 gallon, 55 gallon drums and 275 gallon totes.

**Color:** White

**Finish:** Flat

**Surface Preparation:** Natural grass and synthetic field should be dry and free from any loose materials.

**Application Equipment:** Apply Acrylitex Field Marking Paint with standard field striping equipment. Respirator not required but recommended. Clean tools, equipment and skin with soapy water and rinse.

**Application:** Product is bucket ready. No thinning necessary. Apply when ambient temperature is between 50 and 90 degrees F.

Acrylitex Field Marking Paint is designed for use for marking lines, numbers or graphics on grass, synthetic and other playing fields. This product can be used on any surface requiring an easy striping coating. Our liability is expressly limited to the replacement of defective product.

For additional information, contact Manufacturer.