

Acrylitex®

PROKOTE™

100% Acrylic Texture Coating



ACRYLITEX PROKOTE™ is a 100% acrylic texture coating. The two-coat system was formulated to go over interior drywall, plaster and cured concrete for a highly durable finish. ProKote can be used to create orange peel, splatter and knockdown textures.

Mildew Resistant Coating

Ideal for High Traffic Areas

More Durable than Conventional Texture & Paint

Excellent Hold Out when Higher Sheen Topcoats are Specified

Washable

VOC Compliant

Coverage: Basecoat Application – Apply at approximately 250–300 square feet per gallon yielding 7–10 wet mils.

Texture Application – Apply at 100–150 square feet per gallon depending on level of texture desired.

Application: Apply product at can consistency. No thinning is necessary. Use an airless sprayer with a minimum output of 1.1 gallon per minute to apply the basecoat. Texture coat can be applied using hopper gun, portable texture machine or airless sprayer with air assisted atomizer tip. Compressor must have a minimum of 9 cfm.

Dry time: Acrylitex ProKote is dry to the touch in 4–6 hours @ 70°F and 50% relative humidity. Heavier textures may require additional dry time.

Cleanup: Wipe up drips and spills immediately with a wet cloth. Clean tools with soap and water.



Acrylic
Technologies, Inc.