



ACRYLITEX®
QWIK PREP®
280-0-17

Product Description

Acrylitex Qwik Prep® is a fast drying primer designed to equalize the porosity differences between the drywall face paper and joint compound in new drywall construction. Qwik Prep® has excellent hide and very white in color so you can easily see your pattern when spraying texture. It provides a uniform surface that minimizes “Joint Banding” and “Photographing” of the finish coat.

Performance Features

- **Fast Drying**
- **Excellent Hide**
- **Minimizes “Joint Banding” and “Photographing”**
- **Non Abrasive Equipment Friendly Product**
- **VOC Compliant**
- ✔ **Qualifies for LEEDv4 Credit**
- ✔ **Compliant with CDPH Standard Method v1.2 2017 Emissions**

Compliance - Performance - Certification

- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ SCAQMD Compliant
- ✓ LEED v3.0 Compliant
- ✓ **Member: National Paint Alliance (NPA)**

Product Specifications

Resin Type:	Polyvinyl Acetate
Color Range:	White
Finish:	0-5 @ 60° MPI Gloss Level 1
Drying Time: (70° F. & 50% R.H.)	To Touch: 1 hour To Recoat: 4 hours
Practical coverage:	300-400 sq. ft. per gallon
Recommended Film Thickness:	Wet: 4-6 mils Dry: 1.5 mils
Weight per Gallon:	12.5 lbs.
Solids by Weight:	54.43% ± 2%
Solids by Volume:	32% ± 2%
Sizes:	Five gallon, 55 gallon Drums and 275 gallon Totes
VOC:	<15 g/L
Clean Up:	Water

Surface Preparation

General:

All surfaces must be cured, firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating.

De-gloss shiny surfaces by lightly sanding*. Repair cracks and fill voids.

*See warning for existing lead-based paint under Precautions.

New Surfaces: Follow general surface preparation guidelines. Mask all adjacent areas not specifically intended to receive coating system application. Product is recommended for application to new substrates only.

1. Surfaces must be clean, dry, sound and properly cured.
2. Surfaces must be free of sanding dust, dirt, oil, grease, or other contaminants.
3. Surfaces must be free of chalking, blistering, peeling, cracking and delamination.

Continued Next Page

QWIK PREP® (cont.)

System Recommendations:

Wallboard

Prep Coat: Qwik Prep®

Texture: Spray Applied

Application:

- **Brush:** Use a Nylon/Polyester Brush
- **Roller:** Use 3/8" – 3/4" nap synthetic cover
- **Spray – Airless:** Use .017" - .021" Tip Size

Do not apply when material, air, and/or surface temperature is below 45°. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks. Keep product from freezing.

Thinning

Product is bucket ready. No thinning necessary.

Precautions

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

WARRANTY

Limited Warranty: Acrylic Technologies, Inc. warrants to the purchaser that this product will provide satisfactory performance when applied according to label directions. If this product does not perform to specifications, return unused portion along with sales receipt to place of purchase. As the sole remedy to purchaser, dealer will, at its option: provide additional product to correct affected areas, replace with product of equal value or refund the purchase price paid for this paint product. Failures caused by poor surface preparation, improper application or a breakdown of the underlying surface of previous paint film are not covered by this warranty. ***THIS WARRANTY SPECIFICALLY EXCLUDES LABOR OR COST OF LABOR OR INCIDENTAL OR CONSEQUENTIAL DAMAGES ASSOCIATED WITH THE USE OF THIS PRODUCT.***

DISPOSAL

Never pour leftover coating down any sink or drain – use up material on the job or seal can and store safely for future use. Do not incinerate closed containers. For specific disposal or recycle guidelines, contact your local waste management agency or district. Always attempt to recycle whenever possible.