

# Acrylitex®

## QWIK PREP PLUS™

### Hi-Build PVA Primer



ACRYLITEX QWIK PREP PLUS™ is a high quality PVA product that may be applied in a spray or roll-on application to achieve a level 5 finish. It takes a level 4 finish to a level 5 without the need to skim coat by hand, eliminating the intensive labor required with the traditional method. This product may be sanded and has exceptional hide. Acrylitex Qwik Prep Plus seals the porosity differences between the joint compound and the face paper providing a uniform surface that minimizes “Joint Banding” or “Photographing” of the finish coat.

**Hi-build PVA primer**

**Replaces traditional skim coat to achieve a level 5 finish**

**Exceptional hold out**

**Non-abrasive equipment friendly product**

**VOC compliant**

Coverage: Apply at 250–300 square feet per gallon yielding 5–6 wet mils. To achieve a level 5 finish, apply at 100–150 square feet per gallon, yielding 6–10 wet mils. Easily sands between coats if necessary.

Application: Apply product at can consistency. No thinning is necessary. Use an airless sprayer with a minimum output of 1/2 gallon per minute. Rolling Qwik Prep Plus, use a 3/8”–1/2” nap synthetic roller cover. Lightly sand to remove any unwanted stipple.

Dry Time: Qwik Prep Plus is dry to the touch in 1 hour and ready for recoat in 4–6 hours @ 70°F and 50% relative humidity. Higher film build for a level 5 finish may require additional dry time.

Cleanup: Wipe up drips and spills immediately with a wet cloth. Clean tools with soap and water.



**Acrylic**  
Technologies, Inc.