

# **SAFETY DATA SHEET (SDS)**

# 1. PRODUCT AND COMPANY IDENTIFICATION

PROUDCT IDENTIFICATION:

**Product Name:** ACRYLITEX® BLOCK FILL

Product Number: 296-0-17 WHITE
Product Use: Water-thinned Paint

**MANUFACTURER:** 

Acrylic Technologies, Inc. 8914 NE Alderwood Road Portland, Oregon 97220 www.acrylitex.com

**Manufacturer's Phone:** 503.282.2591 **Emergency (24-hour) Phone:** 800.424.9300

**Date of preparation:** October 27, 2019

## 2. HAZARDS IDENTIFICATION

**Hazard Statement:** This mixture does not meet the criteria for classification.

**Primary Routes of Exposure:** Eye contact, Skin contact, Inhalation, Ingestion

**Potential Acute Exposure Effects:** 

Eyes: May cause slight irritation

Skin: May cause mild irritation

**Inhalation:** May cause irritation of respiratory tract

**Ingestion:** May be harmful if swallowed

#### Overexposure signs/symptoms:

**Eyes:** Watering, redness or irritation

**Skin:** Irritation, dryness

**Inhalation:** Respiratory tract irritation, coughing

**Ingestion:** No specific data

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

REPORTABLE COMPONENTS	CAS NUMBER	% by WEIGHT
Calcium Carbonate	1317-65-3	40 – 55
Titanium Dioxide	13463-67-7	0 - 5

#### 4. FIRST AID MEASURES

**Eyes:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**Skin:** Remove contaminated clothing. Wash thoroughly with soap and water.

**Inhalation:** Move to fresh air. Seek medical attention if symptoms continue. **Ingestion:** Do not induce vomiting. Get medical attention immediately.

#### 5. FIRE FIGHTING MEASURES

Flammable Properties: This product is not flammable

Extinguishing Media: Use foam, carbon dioxide, dry powder, water fog , or an extinguishing agent

appropriate for the surrounding fire.

**Unusual Fire and Explosion Hazards:** Closed containers may rupture or explode when exposed to extreme heat (due to build-up of pressure). During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately

apparent. Obtain medical attention.

**Protective Equipment:** Firefighters should wear self-contained breathing apparatus and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Prevent further leakage or spillage. Soak up with inert absorbent material and transfer to a suitable container for proper disposal.

#### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray mists or

sanding dust. Provide adequate ventilation. Wear appropriate respiratory equipment if

ventilation is inadequate. Wash thoroughly after handling.

**Storage:** Keep container closed when not in use. Transfer only to properly labeled containers.

Keep out of reach of children.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

	OSHA TWA	ACGIH TWA	OSHA STEL
Calcium Carbonate (d)	15 mg/m3	10 mg/m3	not established
Titanium Dioxide (d)	15 mg/m3	10 mg/m3	not established

(d): Hazardous as dust when product is sanded

**Engineering Measures:** Use only in well ventilated areas. Ensure adequate ventilation,

especially in confined areas.

**Personal Protective Equipment:** 

**Eye / Face Protection:** Wear safety glasses or goggles.

**Skin Protection:** Protective gloves and impervious clothing

Respiratory Protection: If exposure cannot be controlled below acceptable limits by

ventilation, use an appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all manufacturers' instructions.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Various

Odor:

Vapor pressure:

Odor threshold:

Vapor density:

Little or no odor

Not available

Not available

**pH:** 8 to 10

Density:12.6 (lbs / gal)Viscosity:125 - 130 KUMelting/freezing point:Not availableSolubility (water):Not availableBoiling point / range:Not availableFlash point:Not available

**Evaporation rate:** < 1 (butyl acetate = 1.0)

Upper flammability limit:Not availableLower flammability limit:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not available

#### 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

Conditions to avoid: None known.

**Materials to avoid:** Strong oxidizing agents and strong acids.

**Hazardous Decomposition Products:** None under normal use. **Hazardous Polymerization:** None under normal conditions.

### 11. TOXICOLOGICAL INFORMATION

**Acute effects:** 

Titanium Dioxide: Oral LD50 (rat): >10,000 mg/kg

Dermal LD50 (rabbit): >10,000 mg/kg Inhalation LC50 / 4 hour (rat): >6.8 mg/l

In February 2006, IARC concluded. "There is inadequate evidence in humans for the carcinogenicity of titanium dioxide." IARC's Monograph 93 reports there is sufficient evidence of carcinogenicity in rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans. It is an IARC Group 2B listed material. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint"

#### 12. ECOLOGICAL INFORMATION

No data available

#### 13. DISPOSAL CONSIDERATIONS

**Disposal Instructions:** Do not allow material to drain into sewers/water supplies. Dispose of in

accordance with all federal, state and local regulations. Consider recycling.

#### 14. TRANSPORT INFORMATION CONSIDERATIONS

Not regulated

### 15. REGULATORY INFORMATION

#### USA

- TSCA Status: All ingredients in the product are listed on the TSCA inventory.
   No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.
- California Proposition 65: This product may contain substances known to the State of California to cause cancer: Quartz silica (airborne particulates of respirable size).

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

#### 16. OTHER INFORMATION

**Hazardous Material Identification System (USA)** 

Health: 1
Flammability: 0
Physical Hazard: 0

Prepared by: Acrylic Technologies, Inc.

The information contained herein is presented in good faith and is believed to be accurate as of the date prepared. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information available to them.